

TU 12 Tank Unit

for Hazardous area Zone 2 with pumps and agitator

A single 12m³ (75 BBL) compartment tank containing an independent paddle mix system. This unit are designed specifically for applications in 3G areas (Zone 2) and is CE, NORSOK Z-015, DNV 2.7-3 and ATEX Zone 2 compliant. The unit can operate in ambient temperatures from -20° C to +50° C. Unit sound pressure level (SPL) is equal or below 83 dBA @ 1m according NORSOK Z-015 requirements.

Features:

- Hydraulic driven agitator and 1 x screw pump.
- Central operator panel.
- Tank housed in a strong crash frame.
- Small footprint.
- Quick and easy rig up.
- Certified to be lifted with content. DNV 2.7-3.
- Powered by external HPU or auxiliary hydraulic power.

About Enerion:

Enerion is a leading provider of products and services to the energy sector. We have extensive experience in engineering, manufacturing and service of equipment and are committed to deliver flexible and future oriented solutions to our customers.



Technical data:

Max input hydraulic flow	: 160 lpm
Max input hydraulic pressure	: 210 bar

Tank:

Design	: 12 m ³ (75 BBL), atmospheric tank. Pump suction. Flat bottom.
Piping material	: Carbon steel (A105)
Tank material	: Carbon steel (A105)
Valves	: 6 of hydraulic knife gate valves

Pump:

Charge pump	: Seepex progressive cavity pump
Charge pump motor	: 100LPM @ 210 bar
Max flow	: 50m ³ /h @ bar

Agitator:

Agitator	: Gann GM-15-H-HD, vertical, double blades, and bearings
Agitator hydraulic motor	: 60LPM@210BAR. Agitator max speed 60RPM
Agitator max torque	: 2767 Nm (at 210BAR at 85% efficiency)

Enerion AS

Plogfabrikkvegen 20
N-4353 Klepp Stasjon
Norway

Enerion Ltd

Bourtie Industrial Park, Inverurie,
Aberdeenshire, AB51 0HL
UK

24/7: +47 51 31 43 00

E-mail: post@enerion.com

Web: www.enerion.com



TU 12 Tank Unit

for Hazardous area Zone 2 with pumps and agitator



Interface:

Air	: 5 – 8 BAR, 1" Chicago claw coupling
Filling connection	: 4" Hammerlug Fig 206 female (no wings)
Discharge connection	: 4" Hammerlug Fig 206 female (no wings)
Filling connection at top	: 4" Hammerlug Fig 206 female (no wings)
Drain connection in tank	: 4" Hammerlug Fig 206 female (no wings)
Hydraulic supply	: 1" quick connection (Snaptite 75 Female)
Hydraulic return	: 1" quick connection (Snaptite 75 Male)
Hydraulic leak	: ½" quick connection (Faster VVS Female)

Approvals:

CE marked	: Yes
ATEX	:  II 3G IIB T4
Lifting	: DNV 2.7-3, EN 12079
NORSOK	: Z-015:2020

Weight & Dimensions:

Length	: 2500 mm
Width	: 2500 mm
Height	: 3700 mm
Tare	: 6100 kg
Max Gross Weight	: 32 500 kg
Payload	: 26 400 kg



Enerion AS

Plogfabrikkvegen 20
N-4353 Klepp Stasjon
Norway

Enerion Ltd

Bourtie Industrial Park, Inverurie,
Aberdeenshire, AB51 0HL
UK

24/7: +47 51 31 43 00

E-mail: post@enerion.com

Web: www.enerion.com

